



รอกสลิงไฟฟ้า “โตโย” แบบรางเดี่ยว (Mono Rail Type)

รุ่น (Model)	YE-10	YE-10H	YE-20	YE-20H	YE-30	YE-30H	CE-51	CE-51H	CE-75	CE-100
Rated load (ขนาด) / ตัน	1.00	1.00	2.00	2.00	3.00	3.00	5.00	5.00	7.50	10.00
Lift/ระยะยก (เมตร)	6.00	12.00	6.00	12.00	6.00	12.00	6.00	12.00	6.00	12.00
ความเร็วแนวตั้ง (ม./นาที)	8.4	8.4	6.70	6.70	5.00	5.00	4.20	4.20	4.20	3.00
มอเตอร์ (kW-P)	1.7-4	1.7-4	2.9-4	2.9-4	3.4-4	3.4-4	5.5-4	5.5-4	7.5-4	7.5-6
ความเร็วซ้าย-ขวา (ม./นาที)	21.00	21.00	21.00	21.00	21.00	21.00	12.50	12.50	12.50	12.50
มอเตอร์ (kW-P)	0.20-4	0.20-4	0.75-4	0.75-4	0.75-4	0.75-4	0.75-4	0.75-4	0.75-4	1.5-4
ขนาด*จำนวนของสลิง (ม.ม.)	2*8.0	2*8.0	2*10.0	2*10.0	2*12.5	2*12.5	4*11.2	4*11.2	4*14.0	4*16.0
น้ำหนัก (ก.ก.)	166.00	200.00	300.00	335.00	320.00	355.00	630.00	740.00	940.00	1400.00
Min I-beam	150*75	150*75	200*100	200*100	250*125	250*125	250*125	250*125	300*150	300*150
Radius of curve	1.80	1.80	2.00	2.00	2.00	2.00	3.00	3.00	3.00	3.50

รอกสลิงไฟฟ้า “โตโย” แบบรางคู่ (Double Rail Type)

รุ่น (Model)	YEW-20	YEW-20H	YEW-30	YEW-30H	CEW-51	CEW-51H	CEW-75	CEW-100	CEW-200
Rated load (ขนาด) / ตัน	2.00	2.00	3.00	3.00	5.00	5.00	7.50	10.00	20.00
Lift/ระยะยก (เมตร)	6.00	12.00	6.00	12.00	6.00	12.00	6.00	12.00	12.00
ความเร็วแนวตั้ง (ม./นาที)	6.70	6.70	5.00	5.00	4.20	4.20	4.20	3.00	3.00
มอเตอร์ (kW-P)	2.9-4	2.9-4	3.4-4	3.4-4	5.5-4	5.5-4	7.5-4	7.5-6	15.00-6
ความเร็วซ้าย-ขวา (ม./นาที)	21.00	21.00	21.00	21.00	12.50	12.50	12.50	12.50	12.50
มอเตอร์ (kW-P)	0.75-4	0.75-4	0.75-4	0.75-4	0.75-4	0.75-4	0.75-4	1.5-4	2.2-4
ขนาด*จำนวนของสลิง (ม.ม.)	2*10.0	2*10.0	2*12.5	2*12.5	4*11.2	4*11.2	4*14.0	4*16.0	4*22.4
น้ำหนัก (ก.ก.)	350.00	395.00	370.00	415.00	665.00	765.00	1120.00	1700.00	3150.00
ขนาดรางวิ่งน้ำ	38*38	38*38	38*38	38*38	38*38	38*38	38*38	50*50	50*50

ชุดขับเคลื่อน (Saddle Unit)



Span(m) Capacity(tf)	6	7	8	9	10	11	12	13	14	15
0.5			LA-10						LAW-25	
1.0			LA-10						LAW-25	
2.0			LA-25						LAW-28	
3.0			LA-25			LA-45			LAW-28	
5.0					LB-45					
7.5					LB-60					
10					LB-90					
15					LB-160					

Specification Table

Saddle type	Basic capacity(tf)	Capacity of wheel pressure(tf)	Travelling speed(m/min)		Speed-reduced motor		Travelling wheel		Travelling rail (kg/m)	Wt. of one set(kg)	Bearing number
			50Hz	60Hz	type	MOTOR (kW-P)	material	M-NT			
L A - 10	1	1.2	21	25	ETG-20	0.2-4	S45C	3-46	12~15	130	6206z
L A - 25	2	2.2	19	23	ETG-33	0.3-4	NSP-80	4-64	12~22	320	6208z
L A - 28	3	2.4	25	30	ETG-76	0.75-4	NSP-80	4.5-58	15~22	410	6308z
L A - 45	5	4.5	25	30	ETG-76	0.75-4	NSP-80	4.5-58	15~22	580	6309z
L A - 60	7.5	6	21	25	ETG-91	0.75-4	NSP-80	4-72	15~22	620	6312z
L A - 90	10	9	21	25	ETG-92	1.5-4	NSP-80	4-85	30~50	700	6314z
L A - 160	15	16	21	25	ETG-92	1.5-4	NSP-80	4-97	30~50	1100	6316z